

**CRANE**

FLUID SYSTEMS

# ProComm Instruments

ELECTRONIC COMMISSIONING UNIT

- Convenience
- Time Saving
- User-friendly design
- Two models available



**IMPORTANT CONNECTION PROCEDURE**

1. Connect red and blue tubes to balancing valve
2. Ensure both isolating valves on hoses are closed
3. Ensure equalising valve on the ProComm is OPEN
4. Attach tubes to the ProComm
5. Open isolating valves - unit will now purge
6. Close both isolating valves and press 'ZERO' on ProComm
7. Open isolating valves
8. Close equalising valve to read differential pressure
9. Open equalising valve prior to removal of tubes

200 kPa max dp

OUR GENIUS IS VALVES

**CRANE**

BUILDING SERVICES & UTILITIES

# ProComm

## Electronic Commissioning Unit with Application Software



The ProComm is an electronic manometer, which is designed to measure differential pressures primarily on balancing valves within water-based HVAC systems. Two options are available Standard Pressure 0.5 kPa - 200 kPa and High Pressure 2.0 kPa to 600 kPa. The ProComm is offered as a complete replacement for a traditional 'water box' and is the obvious choice for today's commissioning engineers. The performance characteristics of over 4,500 valves - from 70 manufacturers are pre-programmed into the ProComm and this extensive knowledge base is continually being updated as new valves are introduced onto the market.

Each unit is supplied with Project Application Software which allows the user to set out a project on a PC with the ability to define floors, groups, branches etc and drag and drop valves into each of these areas. Once prepared, the commissioning schedule for the project can be loaded to the ProComm for use on-site.

## FEATURES

### > Convenience

Compact and lightweight and supplied in a carry case with connection tubes, Binder-style adapters and an assortment of commissioning accessories.

### > Time saving

Each unit is supplied with Project Application Software which can be loaded onto a Windows™ PC to enable a project to be defined prior to attending site.

### > User-friendly design

Small enough to be held in the palm of one hand and with nine button keypad to allow quick and simple navigation of the menu structure.

### > Higher

Two models available Standard Pressure 0.5 kPa - 200 kPa and High Pressure 2.0 kPa to 600 kPa much higher than traditional water / mercury boxes.

## BENEFITS

- Lightweight, compact and easily transportable.
- Highly accurate measurement of differential pressure.
- Eliminates manual calculations, saving time and reducing risk of errors.
- Storing data from site, and downloading of data to PC for commissioning report.
- Technical support available.
- Covers a wide range of differential pressures.

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Crane Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



## CASE CONTENTS

Each ProComm handset is supplied in a sturdy carry case, fitted with profiled foam inserts which includes:

		QUANTITY
1	Carry case, with profiled foam inserts	1
2	Hand held transducer and display unit in a rubber protector	1
3	Connection tubes with isolating valves	2
4	Angle-pattern, binder-style adapters, 3.3mm diameter	2
5	Straight-pattern, binder-style adaptors, 2.0mm diameter	2
6	A set of T-handle Hex keys (3mm, 4mm, 5mm, 6mm and 8mm)	1
7	Screwdriver	1
8	PP3 batteries	2
9	Lanyard	1
10	Strainer maintenance kit	1
11	Calibration certificate	1
12	Quick-Start Guide	1
13	Instruction manual	1

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Crane Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

# PRE-SET DEFAULTS

	ProComm	ProComm - HP
Accuracy	+/- 1% of reading or +/- 0.1 kPa, whichever is the greater	+/- 1% of reading or +/- 0.2 kPa, whichever is the greater
Max Allowable Static Pressure	10 bar	20 bar
Measurement Range	0.5 kPa to 200 kPa	2 kPa to 600 kPa

	WEIGHT (kg)
ProComm Handset *	430g
ProComm-HP Handset *	410g

\* Stated weights are with no battery fitted and exclude rubber protective boot.

	SET DEFAULT	OPTIONS
Language	English	French, Italian, Spanish, Norwegian, Swedish
Pressure Units	kPa	Pa, psi, bar, H <sub>2</sub> O, IWGA, FtHD
Flow Units	l/sec	l/min, 1/hr, USGPM, UKGPM, m <sup>3</sup> /hr, m <sup>3</sup> /m, m <sup>3</sup> /s
Display Options	Flow/Pressure	Multi Display, Pressure, About
Damping Options	Update time	from 1.00 sec to 2.55 sec (default - 1.00 sec)
	Sample time	from 0.6 sec to 11.0 sec (default = 3.0 sec)
Advanced	Flow Alerts - Disabled	Enabled
	Back-Light Timer - 5min	1min, 5min, 10min, Always On
	Auto Off Timer - 5min	1min, 5min, 10min, Always On
	View Size As - mm	Inches
Specific Gravity	1.0	User Defined



To visit our Video Library go to:  
[www.youtube.com/user/CraneBSU](http://www.youtube.com/user/CraneBSU)



FLUID SYSTEMS



FM311  
 ISO 9001



CRANE HOUSE, EPSILON TERRACE  
 WEST ROAD, IPSWICH  
 SUFFOLK IP3 9FJ  
 TELEPHONE: +44 (0)1473 277300  
 FAX: +44 (0)1473 277301  
 EMAIL: [enquiries@cranefs.com](mailto:enquiries@cranefs.com)

[www.cranefs.com](http://www.cranefs.com)

- Designed and manufactured under quality management systems in accordance with BS EN ISO 9001-2008

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Crane Fluid Systems assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within this publication and reserves the right to change without notice. We hope that our communications have an impact on you, but not on the environment. We have taken steps to ensure this leaflet is printed on FSC material and the paper is made by a totally chlorine free process.

CFS\_ProComm\_0617  
 v1



BUILDING SERVICES & UTILITIES

[www.cranesu.com](http://www.cranesu.com)

