

D886 with Thermostatic Control Head T90

Hydraulic Characteristics of Thermostatic Valves with Straight Connections

D886



Features & Benefits

- Complete with compression adaptor allows for installation onto either threaded or smooth pipe to suit site requirements

| CODE | DESCRIPTION | SIZE | KV (m ³ /h) PROPORTIONAL BAND (K) | | | | | KVS |
|------|--------------------------------|------|---|------|------|------|------|-----|
| | | | 1 | 1.5 | 2 | 3 | | |
| D886 | Universal TRV/Wheel Valve Body | 1/2" | 0.32 | 0.50 | 0.67 | 0.86 | 1.52 | |
| D886 | Universal TRV/Wheel Valve Body | 3/4" | 0.43 | 0.63 | 0.82 | 1.05 | 2.20 | |
| D888 | Lockshield Valve | 1/2" | 0.32 | 0.50 | 0.67 | 0.86 | 1.52 | |
| D888 | Lockshield Valve | 3/4" | 0.43 | 0.63 | 0.82 | 1.05 | 2.20 | |

Kv = volume flow in m³/h producing pressure drop 1 bar

Kvs = Kv with valve fully open

| CODE | DESCRIPTION | SIZE | NOMINAL FLOW (l/h) | MAX. DIFF PRES. (bar) |
|------|--------------------------------|------|-----------------------|--------------------------|
| D886 | Universal TRV/Wheel Valve Body | 1/2" | 180 | 1 |
| D886 | Universal TRV/Wheel Valve Body | 3/4" | 240 | 1 |
| D888 | Lockshield Valve | 1/2" | 180 | 1 |
| D888 | Lockshield Valve | 3/4" | 240 | 1 |